

Project: 2015-12-04

File:

Item No.	CZ1-1
splitter type	
	K-200T
Equipment	*/DKB/N
Width [mm]	700
Height [mm]	700
Length [mm]	1250
Parts [m]	1,25
Spl. n pcs	2
Gap [mm]	150
Weight [kg]	54
Flow [m3/h]	8500
press. [Pa]	48
Lw [dB(A)]	44
c [m/s]	11,2
De 63 Hz	3
De 125 Hz	9
De 250 Hz	21
De 500 Hz	22
De 1 KHz	24
De 2 kHz	17
De 4 kHz	12
De 8 KHz	12

Price [EU]	351,00
Quant.[pcs]	1
Amount [EU]	351,00
=====	

Silencer or splitter set [] of galvanized steel plate, Mineral wool(bio-soluble), Glas silk surface, type C:alu/steel-surface, T up to 20m/s, TL: 30m/s, C: 14m/s max 100°C(T)/150°C(TL), DK: Tightness class (DIN EN 1507), N,M,H:Press.range(VDI 3803) Without additional measures the attenuation is valid to the limit attenuation. A= absorber type, K= chamber type, R= resonance type, C= Foil-resonance type L=Perforated sheet metal, T= glass silk, S= Flow profile, B= BetaStream profile W=Angle frame F=Sheet covering G=Counterframe, * RAL-Gz 595, []= Set of splitters, (...)= alternative position, not allowed for in sum total